Mansoura Engineering Journal

Volume 44 | Issue 4

Article 3

10-19-2019

Using Urban Carrying Capacity (UCC) as a Tool for Evaluating Infrastructure of New Egyptian Cities to Promote Sustainable Development. Case Study: 10th of Ramadan City.

Shaimaa Mansour Teaching Assistant, Dep. of Architectural Engineering, Mansoura Higher Institute of Engineering and Technology, arch_shaimaa92@yahoo.com

Ahmed Eltantawy EL-Maidawy Lecturer of Architecture Department of Architecture -Faculty of Engineering - Mansoura University, eltantawy_a@yahoo.com

Ibrahim Hegazy Associate Professor in Architecture- Dep., Faculty of Engineering, Mansoura University, i.hegazy@ymail.com

Follow this and additional works at: https://mej.researchcommons.org/home

Recommended Citation

Mansour, Shaimaa; EL-Maidawy, Ahmed Eltantawy; and Hegazy, Ibrahim (2019) "Using Urban Carrying Capacity (UCC) as a Tool for Evaluating Infrastructure of New Egyptian Cities to Promote Sustainable Development. Case Study: 10th of Ramadan City.," *Mansoura Engineering Journal*: Vol. 44 : Iss. 4, Article 3.

Available at: https://doi.org/10.21608/bfemu.2019.119603

This Original Study is brought to you for free and open access by Mansoura Engineering Journal. It has been accepted for inclusion in Mansoura Engineering Journal by an authorized editor of Mansoura Engineering Journal. For more information, please contact mej@mans.edu.eg.



Using Urban Carrying Capacity (Ucc) As A Tool for Evaluating Infrastructure of New Egyptian Cities to Promote Sustainable Development. Case Study: 10th of Ramadan City استخدام القدرة الاستيعابية الحضرية كأداه لتقييم البنية التحتية للمدن المصرية الجديدة من أجل تعزيز التنمية المستدامه. در اسه الحاله : مدينه العاشر من رمضان

Shaimaa.A. Mansour, Ahmed El-Tantawy and Ibrahim. R. Hegazy

الملخص العربي:- يتزايد النمو الحضري بشكل مطرد في العالم النامي ، وفقًا لتقرير الأمم المتحدة للسكان في العالم لعام 2007. وتؤدى هذه الزيادة إلى تدهور البيئة الحضرية بسبب عدم قدرتها على استيعاب متطلبات السكان. ويظهر هذا الندهور بشكل اكبرفى عناصر البيئة الحضرية بسبب عدم قدرتها على استيعاب متطلبات السكان. ويظهر هذا الندهور بشكل اكبرفى عناصر البيئة الحضرية بسبب عدم قدرتها على استيعاب متطلبات السكان. ويظهر هذا الندهور بشكل اكبرفى عناصر البيئة الحضرية بسبب عدم قدرتها على استيعاب متطلبات السكان. ويظهر هذا الندهور بشكل اكبرفى عناصر البيئة التحضرية بسبب عدم قدرتها على استيعاب متطلبات الحيد لتستطيع استيعاب احتياجات الحاضر والمستقبل. يحظى مفهوم القدرة الاستيعابية لعاصر البيئة الحضرية بعلى المعدور الاستيعابية لعاصر البيئة الحضرية على المستوى العالمي ، وتم تطوير منهجية التقييم القدرة الاستيعابية الحضرية (UCC) في المدن ، حيث تتناول احد جوانبها تقيم حالة البيئه التحتيه فى البيئة الحضرية على المستوى العالمي ، وتم تطوير منهجية البيئه التحضرية على المستوى العالمي ، وتم تطوير منهجية البيئه الحضرية وي القدرة الاستيعابية الحضرية (UCC) في المدن ، حيث تتناول احد جوانبها تقيم حالة البنيه التحتيه فى البيئه الحضرية . ودر استها ، والتركيز على البيئه الحضرية إلى تسليط الضوع على هذه المنهجية ودر استها ، والتركيز على المصريه الدنسيا الرضي في هذه المنهجية ودر استها ، والتركيز على المدن البيئه التحرية والحضرية المصرية . ودر البيها الحضرية المصرية الحضرية الرائيسيه وهى ؛ (البنية التحتية والخدمات الحضرية). ودر المنها من ذل مدن المورفة المصريه المصرية المدن المينية الحضرية المعتدامه بها. وذلك من خلال دراسه وتحليل الوضع المصري الراهن لاحد نماذج المدن الجديده فى مصر (مدينة العاشر من رمضان)، ثم تطبيق تلك المنهجيه لتقيم الحضري المصري تلم من رمضان)، ثم تطبيق تلك المنهجيه لتقيم من مرضان المصري الراهن لاحد نماذج المدن الجديدة فى مصر (مدينة العاشر من رمضان)، ثم تطبيق مأن مدينة المان من رمض رمان الحضري الى المن ين قنقو إلى بعض امدادات المرافق والخدمات الأسسية ، حيث يظهر من التقيم أن مدينة رمض رمان رمضان تفتقر إلى بعض امدادات المرافق والخدمات الأساسية ، حيث انها لا تسيو مالمان مدينه رمن ممن ممن رمضان ما محضري الى مان رمض ي ملمان المما من ما مرمن ممان مانق

KEYWORDS: Urban growth, sustainable development, urban carrying capacity (UCC), infrastructure, 10th of Ramadan city.

Abstract— Urban growth is steadily increasing in the developing world, as indicated by the United Nations World Population Report 2007. This expansion leads to the deterioration of the urban environment due to its powerlessness

Received: (25 March, 2019) - revised: (14 October, 2019) - accepted: (29 October, 2019)

Architect. Shaimaa Ahmed Omar El-Desouky Mansour, Teaching Assistant, Dep. of Architectural Engineering, Mansoura Higher Institute of Engineering and Technology. (Email: arch_shaimaa92@yahoo.com)

Assoc. Prof. Dr. Ahmed ElTantawy ElMaidawy, Associate Professor in Architecture- Dep., Faculty of Engineering, Mansoura University. (Email: Eltantawy_a@yahoo.com).

Assoc. Prof. Dr. Ibrahim Rizk Hegazy, Associate Professor in Architecture- Dep., Faculty of Engineering, Mansoura University. (Email: i.hegazy@ymail.com) to accommodate population prerequisites. This weakening is increasingly obvious in the infrastructure elements, which need protection and good use to accommodate the necessities of the present and future. The concept of carrying capacity of the elements of the urban environment has the attention of many authorities worried about support urban sustainability globally, and a methodology for the assessment of urban carrying capacity (UCC) has been developed in cities, one part of which is assessing the condition of infrastructure in the urban environment. Therefore, the paper aims to study and feature this methodology, and spotlight on one of its main aspects, namely: (infrastructure and urban services). And study the plausibility of applying it to the new Egyptian cities as a way to promote sustainable urban development. This continue by studying and analyzing the current urban circumstance of one of the new urban communities' models in Egypt "tenth of Ramadan City", and

afterward applying the (UCC) methodology to assess the condition of the city's infrastructure, and to identify causes of its shortcomings. Where the assessment shows that the city of "10th of Ramadan" lacks some supplies of basic facilities and services, as it does not accommodate the local population, causing the emergence of some urban problems in the city, and the weak ability to accommodate the target population.

I.INTRODUCTION

HROUGHOUT the world, and in the developing world in particular, many problems have emerged in the urban environment of cities. Specially, in the infrastructure elements. This has impeded the achievement of sustainable development. In this way, urban expansion had viewed as perhaps the best answer to deal with rapid urbanization around the globe. Also, the undertaking for building new urban areas in Egyptian desert was a piece of this undertaking. However, the old forty years' involvement of setting up new urban communities within the Egyptian desert is progressing with a constrained success in achieving the goals of sustainable urban development.

Because of the frail ability of infrastructure to accommodate the requirements of the population in cities, it is in need to be developed with good use to accommodate the needs of the present and the future. Consequently, there was a need for continuous systematic evaluation to assess of the carrying capacity of the infrastructure elements with steps of sustainable development. The concept of carrying capacity of the urban elements has the attention of many authorities concerned with support urban sustainability globally, and a methodology for the assessment of urban carrying capacity (UCC) has been developed in cities, one aspect of which is assessing the state of infrastructure in the urban environment.

The research paper aims to study the methodology of urban carrying capacity, and focus on one of its aspects, namely: (*infrastructure and urban services*), and study the possibility of applying it to one of the new cities in Egypt "10th of Ramadan City". The study begins by analyzing the current urban situation in the city, and then conducting the assessment using the (UCC) methodology, through which it can identify the reasons for the weakness in the carrying capacity of the infrastructure in the city, making it easy to deal with them. So, this methodology is a very good mean for planners and city managers to make decisions for infrastructure, services, and management urban.

II.CONCEPT OF CARRYING CAPACITY

This concept is very wide and has different perspectives, like social, cultural, political, ecological, etc. And it presented firstly by Thomas Malthus in 1798. He anticipated that the earth can only sustain a definite amount of human growth for a definite time. This determine the state of an ecosystem with regard to the compressions forced by population's demands. Where the whole carrying capacity of an area can defined as the maximum limit of population that can be supported by the urban environment of that area through best use of accessible resources, as shown in (Figure 1). It is also not a stable, it can increase or decrease immensely affected by several factors. One of the main factors that much affects the carrying capacity is the extent of using resource and urban facilities, which highly depends on social, cultural and economic status of the people, (ENT, 2012).



Figure 1. The relation between population rise and carrying capacity, Source: (ENT, 2012)

III. COMPONENTS AND LEVELS OF URBAN CARRYING CAPACITY

UCC is not related to ecology or physical infrastructure only, but economic, social, environmental, and institutional aspects as well. One of the highlights of UCC is that it is dynamic and improvable not a static. It can be altered by the interactions between using technology, individual favorites, investing, and production. The main indicators that define the urban carrying capacity for an area are grouped into five major sectors as shown in (Figure 2), (Sarma, 2012).



Figure 2: Main sectors of UCC and their relationships

The suitable indicators were chosen to assess urban carrying capacity according to a number of key principles through a comprehensive review of the literature. The key factors for UCC assessment abridged in 5 levels, each level incorporates some indicators; environmental impacts and natural resources; infrastructure and urban services, public perception; institution setting; and society supporting capacity. (Graymore, 2010).

IV.THE URBAN CARRYING CAPACITY CALCULATION FRAMEWORK

Based on this, (Wei, 2016), addressed key indicators that have been developed into an assessment system. The system involves five groups of variables; (economy, resources,

environment, infrastructure, and transport). The current study, for evaluating the selected case study, focuses on the level of Infrastructure and urban services capacity as explained in (Table 1) and (Table 2). Because of the vital transport role in large cities, this study separates transport from infrastructure as an individually dimension when calculating weights based on the analytical hierarchy process as in the following section.

Table 1
The definition of (Infrastructure and urban services) component concerned with the study

Component	Definition
Infrastructure and urban	It means the volume of human activity that can be supported by urban infrastructure and services in a given area without causing a deterioration in the quality of life. On the basis that demand for supply in urban infrastructure and services should be balanced, as well
services	as the intensity, efficiency and pattern of resource use in infrastructure development.

Dimensions	Indicators	Benchmarks	Ref			
Infrastructure	Basic municipal facilities such as water, electricity, and gas supply and con	mmunication links:				
and urban	Urban gas connection rate (%)	=100%	а			
services	Access rate of Cable TV (%)	=100%	а			
	The normal supply of tap water (days/year)	=365 days/year	а			
	Cultural and recreational facilities:	<u>u</u>				
	The number of libraries per 10 thousand people	≥ 0.3	а			
	The number of museums per 10 thousand people	≥ 0.3	а			
	The coverage rate of free open sports facilities within 1000 meters of residential areas (%)	= 100 %	а			
	Per Capita floor space of houses in urban areas (m2)	\geq 26 m2	а			
	Sports facilities:					
	Public satisfaction rates for sports, education and culture facilities (%)	= 100 %	а			
	Healthcare facilities:					
	Number of hospital bed per thousand persons (%)	\geq 90	а			
	Population life expectancy (years)	\geq 75 years old	а			
	Public traffic:	u				
	Per capita road areas (m2)	≥15 m2	а			
	Public transportation ridership rate (%)	\geq 35% for large and medium cities	а			
	Social parking rate (%)	\leq 150% for large cities \leq 100% for small-medium cities	а			
	Resident's average commuting time (One-way) (%)	\leq 30 minutes	а			
a Refers to in	formation from the Chinese Society for Urban Studies (CSUS) (2007).					

Table 2		
Benchmarks for UCC indicators	(Wei	2015)

V.DETERMINING THE WEIGHT OF INDIVIDUAL INDICATORS

To calculate the weights of the elements of the evaluation criteria in this research, the method of "Analytic Hierarchy Process (AHP)" for criteria elements were used and the estimation based on evaluator's knowledge of sub-criteria. In this method, weights are set for criteria elements according to their relative importance to each other. The weighting and measurement process and its values are summarized in the following steps:

Step (1): Comparing the four main elements of urban carrying capacity assessment according to the importance indications shown in (Table3), leading to the values listed in (Table 4). (Chao-Shi,, 2007).

Step (2): Normalize the cell values resulted in step 1 by dividing the rate of each cell by its column summation and determine the weights by calculating the mean value of each row. See (Table 5).

Step (3): Calculating Consistency Ratio (CR)

 λ_{max} is the principal Eigen Value.



- $\lambda_{\text{max}} = \Sigma$ the products between each element of the priority vector and column totals.
- $\lambda_{\text{max}} = (0.17*6.8) + (0.18*7.8) + (0.26*4.3) + (0.26*4.1) + (0.1*11) \approx 5.38$
- $\mathbf{CR} = (\lambda_{max} n) / n 1$ where (n) is the number of factors.
- $\mathbf{CR} = (5.38 5) / (5 1) \approx 0.095$

Step (4): Calculating Index (CI)

- **CI** = Consistency Ratio (CR) / Random Consistency Index (RI).
- Where (**RI**) can be calculated from the following Saaty's rule as 0.90

Then, CI = CR/RI = 0.095/1.12 = 0.08, (CR< 0.1; Acceptable)

Table 3
Indications of scaling for the Analytic Hierarchy Process (AHP), shown in (Table3)

Importance	Meaning
1	equally important
2	weak
3	the former element is moderate important
4	moderate plus
5	the former element is strong important
6	strong plus
7	the former element is very strong important
8	very, very strong
9	the former element is Extreme important

 Table 4

 Comparing criteria elements using importance indications, adapted from (Saaty, 1980).

	Economy	Resources	Environment	Infrastructure	Transport
Economy	1	3	1/2	1/3	2
Resources	1/3	1	2	1/3	3
Environment	2	1/2	1	2	3
Infrastructure	3	3	1/2	1	2
Transport	1/2	1/3	1/3	1/2	1
Sum (Σ)	6.83	7.83	4.33	4.16	11

 Table 5

 Normalization values and calculate weights, adapted from (Saaty, 1980).

	Economy	Resources	Environment	Infrastructure	Transport	Sum (Σ)	priority vector "Weight" Sum (Σ)/5
Economy	0.14	0.38	0.11	0.07	0.18	0.88	0.177
Resources	0.04	0.12	0.46	0.07	0.25	0.94	0.180
Environment	0.30	0.06	0.23	0.48	0.25	1.32	0.259
Infrastructure	0.44	0.38	0.12	0.24	0.16	1.35	0.260
Transport	0.073	0.042	0.07	0.12	0.09	0.41	0.12

As shown in the four steps above, the authors have developed a judgment matrix for the elements of urban carrying capacity derived from the experiences of previous judgments. And after the calculation of the "consistency ratio", the Consistency Index (CI) is equal to 0.08 and then the degree of consistency proved as satisfactory. When $CI \le 0.1$, the rate between the elements are realistic. Therefore, the weights are acceptable. Then, in the same way, the weight of individual indicators was calculated only for 30 of them, as shown in (Table 6).

Sectors	Indicators	weight
Economy	X1: Urban registered unemployment rate (%)	0.034
(0.177)	X_2 : Per capita disposable income of urban households	0.037
	X3: Per capita Fiscal income (Yuan)	0.033
	X4: Per capita GDP (Yuan)	0.038
	Xs: Annual GDP growth rate	0.034
Resources	X_i : Per capita water supply (ton)	0.030
(0.180)	χ_2 : Per capita daily domestic water consumption (liter)	0.044
	X_3 : Per capita constructive land (m2)	0.037
	X4: Per capita gas supply (m3)	0.031
	X5: Per capita domestic electricity consumption (kwh)	0.037
- · · ·	X1: Industrial wastewater discharged per 10,000 Yuan GRP (ton)	0.039
(0.259)	X2: Industrial CO2 emissions per 10,000 Yuan GDP (kg)	0.029
(0.20))	X_3 : The ratio of industrial solid waste that is used extensively	0.040
	X_4 : The ratio of sewage treated (%)	0.034
	X_s : Living garbage treatment rate	0.029
	X_{d} : The number of days with air quality above Grade-2 standard per years	0.030
	X1: Per capita green area (m2)	0.025
	X_{δ} : Green coverage rate of urban built-up areas (%)	0.032
Infrastructure	X1: Number of hospital beds per 10,000 persons	0.029
(0.260)	X1: Per capita floor space of urban residents (m2)	0.034
	X_3 : The density of drainage pipe in urban built-up areas (km/km2)	0.029
	X4: water access rate (%)	0.037
	$X_{\rm S}$: gas access rate (%)	0.038
	X ₆ : Number of Internet per 10,000 persons (user)	0.030
	X_{5} : Number of mobile phone users per 10,000 persons (user)	0.027
	X_{δ} : Number of fixed telephone users per 10,000 persons (user)	0.035
Transport	X1: Number of bus per 10,000 persons (unit)	0.031
(0.12)	X2: Number of private cars per 10,000 persons (unit)	0.031
	X3: Per-capita urban road areas (m2)	0.036
	X.: Highway density (km/km2)	0.029

 Table 6

 The weight of individual indicators of UCC, Updated from (Wei, 2016)

VI.METHODOLOGICAL STEPS TO ASSESS URBAN CARRYING CAPACITY

The case study methodology passes by three stages as shown in (Figure 3). First of all, the case study will be selected by several target characteristics. Secondly, determine the benchmarks for urban capacity indicators of the city, and compare them with the current situation in the city. Then evaluating the city accordingly and calculate the numerical value of the sector related to infrastructure. The case study procedure depends on six steps to reach the final step embodied in the discussion and conclusion.



Figure 3: The methodology of the case study

A. Case Study Overview:

This step is a summary that shows the basic information of the selected city "10th of Ramadan" (1st Generation), and also discuss the current urban situation, as follow:

B. Basic Information about The City:

10th of Ramadan City, the first new urban industrial cities in Egypt, established by 1980, and it belongs to the (1st Generation) of new cities. Situated on 55 km from Cairo, passing through the city of Al Obour, linked to the Delta region through province of Sharqia, as shown in (Figure 4). The city has a total area of 95 thousand acres, which planned to accommodate (480 thousand) people by 2017, and to accommodate (2.1 million) by 2032. Where the current population actually reached (500,000 people) in 2017. The city is divided into 3 Subdivisions; Knowledge Village, Business and Finance region, Regional Services center, with 8 sub-districts, with a density of 37 person / acre.



Figure 4: The location of "Tenth of Ramadan" City

C. Housing and Buildings Type in The City:

The city had been initially planned for housing all economic sectors of the society, but it has instead been developed as an industrial city over time and the housing intensified on small segment. The total area distributed for housing in the city is 12768 acres. And the housing sector is divided into three axes as follow: *The Residential Units Implemented, Project of Million Housing Units (The Social Housing),* and *Investors plots,* as shown in (Figure 5).



Figure 5: Housing and Buildings Type in tenth of Ramadan City

Finally, the city did not realize its population objectives, where the rate of urbanization did not override 50% from what was planned to be achieved. While industrial development has overrode the main plan expectations, where the number of workers had reached to 225 thousand in 2010, this rise in labor estimated to be more than 300% of what was wanted to be achieved at the end of planning period in 2002.

D. Land Use in the city:

The total area of the city is 95000 acres, while the total urban area is 80368.9 acres. Built up area of the city is designed in a symmetrical shape around a linear axis representing the city center, this symmetry is shown in number of districts and neighborhood, and (Figure 6) shows the current utilization of land for 10^{th} of Ramadan.



Figure 6: Current land use for10th of Ramadan city

E. Transportation in The City:

A system of inner and regional roads along the length of 1140 km was built, follow a clear hierarchy, from the highway "Ismailia and Belbais roads" to the main collectors, working as a ring road for each neighborhood, ending with local streets where walking distances range from 300 to 400 m and do not surpass10 minutes by walking. However, from the field survey, residents claimed that some neighborhood centers are still not present or inadequate, so they must walk to the main city center, as shown in (Figure 7).



Figure 7: Transportation in 10th of Ramadan city

F. Infrastructure in The City:

What has been achieved of facilities in the 36 years since the establishment of the city about 16,900 acres, with rate of 470 acres / year, where the area of facilities being implemented during the last four years 2014/2018 (4444.5 acres). There is still a shortage of infrastructure supplies to cover the entire city, as shown in (Figure 8).



Figure 8: Supply of facilities in Tenth of Ramadan

VII.ASSESSMENT & CALCULATING THE URBAN CARRYING CAPACITYFOR THE SELECTED CITY

First way of assessment, the criteria and data are presented for each indicator of city urban capacity, and the results of the estimate are presented, where "NO" shows that the indicators exceed the UCC limit and need improvements. Some indicators and thresholds were distinguished by (I) due to lack appropriate statistics.

Second way of assessment, estimating the numerical value of the urban carrying capacity for the city by calculating the weights for each indicator within each sector. and weights of the indicators achieved are calculated only in each sector. The total of these weights represents the value of the urban carrying capacity of the sector. Where the total value of urban capacity of the city is the total value of those sectors. The data used has been compiled from several sources, including:

- Ministry of Housing, Utilities and Urban Communities. (MHUUC, 2018)
- New Urban Communities Authority. (NUCA, 2018).
- Central Agency for Public Mobilization and Statistics. (CAPMAS, 2019).
- General Organization for Physical Planning. (GOPP, 2019)

A. Assessment the Urban Carrying Capacity for 10th of Ramadan city	y:
--	----

 Table 7

 Assessment the urban carrying capacity (UCC) for Tenth of Ramadan City

Dimensions	Indicators	Benchmarks	Result	S	R
	Basic municipal facilities such as water, electricity, and gas supply	and communication links:			
Infrastructure	Urban gas connection rate (%)	• =100%	50%	No	b
and urban	Access rate of Cable TV (%)	• =100%	100%	Yes	b
services	The normal supply of tap water (days/year).	• =365 days/year	365 day	Yes	b
	Cultural and recreational facilities:				
	The number of libraries per 10 thousand people.	 ≥ 0.3 	0.001	No	i
	The number of museum per 10 thousand people.	$\bullet \geq 0.3$	Not available	No	i
	The coverage rate of free open facilities/1000 m of residential areas (%)	• = 100 %	Not available	No	i
	Per Capita floor space of houses in urban areas (m^2) .	• $\geq 26 m^2$	(18:30)m ²	Yes	b
	Sports facilities:				
	Public satisfaction rates for sports, education and culture facilities (%)	• = 100 %	90%	No	i
	Healthcare facilities:				
	Number of hospital bed per thousand persons	 ≥ 90 	4	No	b
	Population life expectancy (years).	• \geq 75 years old	73	No	c
	Public traffic:				
	Per capita road areas (m ²).	• $\geq 15 m^2$	2.5m ²	No	b
	Public transportation ridership rate (%)	 ≥ 35% 	25%	No	i
	Social parking rate (%)	• $\leq 100\%$ for small cities	Not available	No	i
	Resident's average commuting time (One-way) (%)	• ≤ 30 minutes	(15:20)	Yes	c
b 10th of Ramad	an City Development Agency. (10RCDA, 2018).	·			
c Report of the C	Central Agency for Public Mobilization and Statistics. (CAPMAS, 2015).				
i indicates that site inspection	information is not specifically provided in the statistical report of the city, but is and field visits.	ut results provided fromprevious stud	lies and questi	onnai	res,

B. Calculating the UCC Value for 10th of Ramadan city:

Sector	Indicators	Benchmark ®	Result		Weight			
	X_{I} : Number of hospital beds per 10,000 persons	(0.029)	≥ 90	4	No			
	X_2 : Per capita floor space of urban residents (m^2)	(0.034)	$\geq 26 m^2$	(18:30) m ²	Yes	0.034		
	X_3 : The density of drainage pipe in urban built-up areas (km/km ²)	(0.029)	$\geq 15 km/km^2$	Not available	No			
Infrastructure	X_4 : water access rate (%)	(0.037)	= 100%	100%	Yes	0.037		
(0.260)	X ₅ : gas access rate (%)	(0.038)	= 100%	50%	No			
	X ₆ : Number of Internet per 10,000 persons (user)	(0.030)	=100%	< 100%	No			
	X_7 : Number of mobile phone users per 10,000 persons (user)	(0.027)	=100%	100%	Yes	0.027		
	X_8 : Number of fixed telephone users per 10,000 persons (user)	(0.035)	=100%	< 100%	No			
	Infrastructure (UCC) = Σ w	eights = 0	0.098					
	X ₁ : Number of bus per 10,000 persons (unit)	(0.031)	≥10000	< 10000	No			
Transport	X_2 : Number of private cars per 10,000 persons (unit)	(0.031)	≥ 5000	7500	Yes	0.031		
(0.12)	X_3 : Per-capita urban road areas (m^2)	(0.036)	$\geq 15 m^2$	2.5m ²	No			
	X ₄ : Highway density (km/km ²)	(0.029)	$= 50 (km/100km^2)$	28 km/100km ²	No			
	Transport (UCC) = Σ weights = 0.031							

Table 8 Calculating the urban carrying capacity's value For the Tenth of Ramadan City

VIII.CONCLUSION

Following the application of the UCC assessment by the two methods on the city of case study, according to the city's strategic plan and the reports of New Urban Communities Authority, and General Organization for Physical Planning, it was discovered that there are some strengths and weaknesses in sector of "Infrastructure and urban services" in terms of their urban capacity, Optimal values for each area of urban capacity, shown in (Figure 9). 10th of Ramadan city with its resources and elements in urban environment is getting near to

the standard limit, but because of misuse, these resources become inadequate. As for infrastructure and services, the city lacks a supply of services, doesn't suit the local population (the weight of carrying capacity for infrastructure 0.098), causing the emergence of some ecological issues which were a natural response to the contradiction of their urban capacity with the needs of the population, and with considering urban carrying capacity in the pre-planning phase of new communities in accordance with the targeted population density, sustainable urban development can promoted.



Figure 9: Evaluation Results of Aspects of UCC Framework for 10th of Ramadan city

REFERENCES

- 10RCDA, 2018. 10th of Ramadan City Development Authority. [Online] Available at: http://www.10ramadancity.net/ [Accessed 5 10 2018].
- [2] CAPMAS, 2015. Central Agency for Public Mobilization and Statistics. [Online] Available at: http://www.capmas.gov.eg/HomePage.aspx [Accessed 5 11 2018].
- [3] CAPMAS, 2019. Central Agency for Public Mobilization and Statistics. [Online] Available at: http://www.capmas.gov.eg/ [Accessed 2 1 2019].
- [4] C.-S. L. Y.-C., 2007. A methodology for evaluation and classification of rock mass quality on tunnel engineering. Tunnelling and Underground Space Technology, 22(4), pp. 377-387.
- [5] ENT, W. A. R. M. A., 2012. URBAN CARRYING CAPACITY. Centre of Excellence, INTEGRATED LANDUSE PLANNING AND WATER RESOURCES MANAGEMENT (ILPWRM).
- [6] GOPP, 2019. General Organization for Physical Planning. [Online] Available at: http://gopp.gov.eg/ [Accessed 2 1 2019].

- [7] Graymore, M. L., S. N. G., R. R. E., 2010. Sustaining human carrying capacity: a tool for regional sustainability assessment. Ecological economics, Elsevier, 69(3), pp. 459--468.
- [8] MHUUC, 2018. Ministry of Housing, Utilities and Urban Communities. [Online] Available at: http://www.mhuc.gov.eg/ [Accessed 25 12 2018].
- [9] NUCA, 2018. New Urban Communities Authority. [Online] Available at: http://www.newcities.gov.eg/english/default.aspx [Accessed 25 12 2018].
- [10] Saaty, W. Y. T. L., 1980. Marketing applications of the analytic hierarchy process. Management science, INFORMS, 26(7), pp. 641--658.
- [11] Sarma, A., M. C., B. R., D. S. a. K. S., K. B. a. S. P., 2012. Urban carrying capacity: Concept and calculation. Centre of Excellence: Assam, India.
- [12] Wei, Y., H. C., L. J., X. L., 2016. An evaluation model for urban carrying capacity: A case study of China's mega-cities. Habitat International, Elsevier, Volume 53, pp. 87-96.
- [13] Wei, Y., H. C., L. P. T., S. Y., F. Y., 2015. Using urbancarrying capacity as a benchmark for sustainable urban development: an empirical study of Beijing. Sustainability, Multidisciplinary Digital Publishing Institute, Volume 7, pp. 3244--3268.